

Mineral Wool Commercial and Industrial Insulation

Version 3.2

Revision Date 05/06/2020

Print Date 05/06/2020

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Trade name : MinWool-1200® Field-Formed Pipe Insulation, MinWool-1200® Flexible Batt, MinWool-1200® Industrial Board, MinWool-1200® Lamella Tank Wrap, MinWool-1200® Metal Mesh Blanket, MinWool-1200® Mitered Fittings, MinWool-1200® Pipe and Tank Wrap, MinWool-1200® Pipe Insulation, MinWool-1200® Precision Cut Pipe Insulation, MinWool-1200® Preformed Pipe Insulation, MinWool® Curtainwall, MinWool® Deck Plug Fire Stop, MinWool® Marine Board, MinWool® Safing, MinWool® Sound Attenuation Fire Batts (SAFB), MinWool® Window Wall

Manufacturer or supplier's details

Company : Johns Manville
Address : P.O. Box 5108
Denver, CO USA 80127
Telephone : +1-303-978-2000
Emergency telephone number : +1-800-424-9300 (CHEMTREC)

Company : Johns Manville Canada Inc.
Address : 5301 42 Avenue
Innisfail, AB Canada T4G 1A2
Telephone : +1-303-978-2000
Emergency telephone number : +1-800-424-9300 (CHEMTREC)

Recommended use of the chemical and restrictions on use

Restrictions on use : For professional and industrial installation and use only.

Prepared by : productsafety@jm.com

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200 (OSHA HCS 2012) and the Hazardous Products Regulations (WHMIS 2015)**

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Chemical nature**

Mineral wool product

Hazardous components

Non-hazardous according to 29 CFR 1910.1200 (OSHA HCS 2012) and the Hazardous Products Regulations (WHMIS 2015), when used as intended.

Mineral Wool Commercial and Industrial Insulation

Version 3.2

Revision Date 05/06/2020

Print Date 05/06/2020

Relevant ingredients

Chemical name	CAS-No.	Concentration (%)
mineral fibers	Not Assigned	>= 95 - <= 100 %
cured urea extended phenol-formaldehyde resin	Not Assigned	>= 0 - <= 5 %

SECTION 4. FIRST AID MEASURES

- General advice : Get medical attention if symptoms occur.
- If inhaled : Move to fresh air.
If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.
Get medical attention if irritation develops and persists.
- In case of eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : If symptoms persist, call a physician.
Rinse mouth with water to remove dust or fibers and drink plenty of water to help reduce irritation.
- Most important symptoms and effects, both acute and delayed : Itching
Temporary mechanical abrasion (itching) of skin, eyes and respiratory tract may occur upon exposure to fibers or dust during handling of this product and cannot occur unless there is direct contact.
Trace amounts of formaldehyde may be released when contacted with moisture, including humidity. This release is most prevalent in conditions of high heat and humidity.
- Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.
- Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Avoid dust formation.

Mineral Wool Commercial and Industrial Insulation

Version 3.2

Revision Date 05/06/2020

Print Date 05/06/2020

Methods and materials for containment and cleaning up : Pick up and arrange disposal without creating dust.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Provide appropriate exhaust ventilation at places where dust is formed.

Advice on safe handling : For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area.

Conditions for safe storage : Keep in a dry, cool place.

Materials to avoid : No materials to be especially mentioned.

Further information on storage stability : Stable at normal ambient temperature and pressure.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Inert or Nuisance Dust, Particulates Not Otherwise Regulated (PNOR)	Not Assigned	PEL (Total dust)	15 mg/m ³	OSHA
		PEL (Respirable fraction)	5 mg/m ³	OSHA

As a member of the North American Insulation Manufacturers Association (NAIMA), JM subscribes to the NAIMA Product Stewardship Program (NPSP). Under the NPSP, JM recommends that exposures be limited to the voluntary concentration of 1 f/cc TWA. The NPSP also includes work practice and respiratory protection recommendations. For more information, see NAIMA's Health and Safety Reference Library (website: <http://insulationinstitute.org/tools-resources/resource-library/health-safety/>) to find the Product Stewardship Program Pocket Folder (N052) and other Fact Sheets.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection
Material : Protective gloves

Remarks : For prolonged or repeated contact use protective gloves.

Eye protection : Safety glasses

Mineral Wool Commercial and Industrial Insulation

Version 3.2

Revision Date 05/06/2020

Print Date 05/06/2020

- Skin and body protection : Wear protective clothing, such as long-sleeved shirts and pants.
Remove and wash contaminated clothing before re-use.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : solid
- Colour : beige, light yellow, tan
- Odour : not significant
- Odour Threshold : No data available
- pH : Not applicable
- Melting point/range : > 2,000 °F
- Initial boiling point and boiling range : Not applicable
- Flash point : Not applicable
- Evaporation rate : Not applicable
- Flammability (solid, gas) : No data available
- Upper explosion limit : Not applicable
- Lower explosion limit : Not applicable
- Vapour pressure : Not applicable
- Relative vapour density : Not applicable
- Relative density : No data available
- Density : Not applicable
- Solubility(ies)
Water solubility : Not applicable
- Solubility in other solvents : No data available
- Partition coefficient: n-octanol/water : No data available
- Auto-ignition temperature : No data available
- Thermal decomposition : Not applicable
- Viscosity

Mineral Wool Commercial and Industrial Insulation

Version 3.2

Revision Date 05/06/2020

Print Date 05/06/2020

Viscosity, dynamic : Not applicable

Viscosity, kinematic : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Stable under recommended storage conditions.
No hazards to be specially mentioned.

Conditions to avoid : No data available

SECTION 11. TOXICOLOGICAL INFORMATION**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.**ACGIH** No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.**OSHA** No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA (29 CFR 1910 Subpart Z, Toxic and Hazardous Substances).**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.**Further information****Product:**

Remarks: Temporary mechanical abrasion (itching) of skin, eyes and respiratory tract may occur upon exposure to fibers or dust during handling of this product and cannot occur unless there is direct contact. Trace amounts of formaldehyde may be released when contacted with moisture, including humidity. This release is most prevalent in conditions of high heat and humidity.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Mineral Wool Commercial and Industrial Insulation

Version 3.2

Revision Date 05/06/2020

Print Date 05/06/2020

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : Due to the properties of the product, a hazard to the environment may not be expected.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

SECTION 14. TRANSPORT INFORMATION**International transport regulations**

Land transport

USDOT: Not classified as a dangerous good under transport regulations

TDG: Not classified as a dangerous good under transport regulations

Sea transport

IMDG: Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO: Not classified as a dangerous good under transport regulations

SECTION 15. REGULATORY INFORMATION**TSCA list**

TSCA - 5(a) Significant New Use Rule List of Chemicals : Not relevant

U.S. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpart D) : Not relevant

EPCRA - Emergency Planning and Community Right-to-Know Act**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

Mineral Wool Commercial and Industrial Insulation

Version 3.2

Revision Date 05/06/2020


Print Date 05/06/2020

SARA 311/312 Hazards : No SARA Hazards

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

California Prop. 65

 **WARNING:** This product can expose you to chemicals including formaldehyde, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

DSL : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION**Further information**

Revision Date : 05/06/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.