


## Klean Strip Odorless Mineral Spirits

HEALTH		1
FLAMMABILITY		2
PHYSICAL		0
PPE		X



Printed: 01/09/2014  
Revision: 09/27/2010

## 1. Product and Company Identification

**Product Code:** LL2127

**Product Name:** Klean Strip Odorless Mineral Spirits

**Manufacturer Information**

**Company Name:** W. M. Barr  
2105 Channel Avenue  
Memphis, TN 38113

**Phone Number:** (901)775-0100

**Emergency Contact:** 3E 24 Hour Emergency Contact (800)451-8346

**Information:** W.M. Barr Customer Service (800)398-3892

**Web site address:** www.wmbarr.com

**Preparer Name:** W.M. Barr EHS Department (901)775-0100

**Intended Use:** For thinning oil-based paint, stain and varnish.

**Synonyms**

QKSP94205CA, GKSP94214CA, QKSP94005CA, QKSP94005LCA, GKSP94006CA, GKSP94006PCA

## 2. Hazards Identification

**GHS Hazard Phrases**

No data available.

**GHS Precaution Phrases**

No data available.

**GHS Response Phrases**

No data available.

**GHS Storage and Disposal Phrases**

No data available.

**Potential Health Effects (Acute and Chronic)****INHALATION:**

Vapor harmful. Danger of serious damage to health by prolonged exposure through inhalation.

**SKIN CONTACT:**

Prolonged skin contact may cause skin irritation and/or dermatitis.

**EYE CONTACT:**

Liquid contact may cause irritation.

**INGESTION:**

Harmful or fatal if swallowed. May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

**CHRONIC EFFECTS:**

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage.

**TARGET ORGANS:** skin, central nervous system

# SAFETY DATA SHEET

## Klean Strip Odorless Mineral Spirits

Page: 2  
Printed: 01/09/2014  
Revision: 09/27/2010

PRIMARY ROUTES OF ENTRY: inhalation, skin contact

### Medical Conditions Generally Aggravated By Exposure

None known.

### OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

## 3. Composition/Information on Ingredients

Hazardous Components (Chemical Name)	CAS #	Concentration
1. Hydrotreated light distillate (petroleum)	64742-47-8	100.0 %

## 4. First Aid Measures

### Emergency and First Aid Procedures

Skin:

Wash the skin thoroughly with water and soap, if available, while removing contaminated clothing. Seek medical attention if irritation develops or persists.

Eyes:

Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes. Seek medical attention.

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Ingestion:

If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person.

### Signs and Symptoms Of Exposure

See Potential Health Effects.

## 5. Fire Fighting Measures

**Flammability Classification:**

NFPA Class IIIA

**Flash Pt:**

> 170 F Method Used: TAG Closed Cup

**Explosive Limits:**

LEL: 0.6 % UEL: 7.0 %

**Autoignition Pt:**

450 F

### Fire Fighting Instructions

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

### Flammable Properties and Hazards

No data available.

### Hazardous Combustion Products

Carbon monoxide, carbon dioxide

### Suitable Extinguishing Media

Use carbon dioxide, dry powder, foam, or water spray / fog.

### Unsuitable Extinguishing Media

None known.

## 6. Accidental Release Measures

### Steps To Be Taken In Case Material Is Released Or Spilled

Isolate the immediate area. Prevent unauthorized entry. Eliminate all sources of ignition in area and downwind of the spill area. Stay upwind, out of low areas, and ventilate closed spaces before entering. All equipment used when handling this product must be grounded or non-sparking. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to compatible containers. For large spills, dike ahead of the spill for possible collection and reuse or disposal.

## 7. Handling and Storage

### Precautions To Be Taken in Handling

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Ensure all equipment is electrically grounded before beginning transfer operations.

Avoid prolonged skin contact.

### Precautions To Be Taken in Storing

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

## 8. Exposure Controls/Personal Protection

Hazardous Components (Chemical Name)	CAS #	OSHA PEL	ACGIH TLV	Other Limits
1. Hydrotreated light distillate (petroleum)	64742-47-8	No data.	200 mg/m3	No data.

### Respiratory Equipment (Specify Type)

For use in areas with inadequate ventilation or fresh air, wear a properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors.

For OSHA controlled work places and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding the appropriate TLV.

A dust mask does not provide protection against vapors.

### Eye Protection

Chemical splash goggles should be worn to prevent eye contact.

### Protective Gloves

Wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as nitrile rubber may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.

### Other Protective Clothing

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

# SAFETY DATA SHEET

## Klean Strip Odorless Mineral Spirits

Page: 4  
Printed: 01/09/2014  
Revision: 09/27/2010

### Engineering Controls (Ventilation etc.)

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air.

### Work/Hygienic/Maintenance Practices

Wash hands thoroughly after use and before eating, drinking, or smoking.

Do not eat, drink, or smoke in the work area.

Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.

## 9. Physical and Chemical Properties

<b>Physical States:</b>	[ ] Gas	[ X ] Liquid	[ ] Solid
<b>Melting Point:</b>	< -94 F		
<b>Boiling Point:</b>	390 F - 480 F		
<b>Autoignition Pt:</b>	450 F		
<b>Flash Pt:</b>	> 170 F Method Used: TAG Closed Cup		
<b>Explosive Limits:</b>	LEL: 0.6 %	UEL: 7.0 %	
<b>Specific Gravity (Water = 1):</b>	0.8102	at 25 C	
<b>Density:</b>	6.84 LB/GL		
<b>Vapor Pressure (vs. Air or mm Hg):</b>	0.05 MM HG	at 20 C	
<b>Vapor Density (vs. Air = 1):</b>	5.9		
<b>Evaporation Rate:</b>	0.02		
<b>Solubility in Water:</b>	Not Soluble		
<b>Percent Volatile:</b>	100 % by weight.		
<b>VOC / Volume:</b>	0 G/L		

### Appearance and Odor

Aromatic hydrocarbon-like odor. Clear liquid.

### Additional Physical Information

This product is not a VOC as defined by the California Air Resources Board (CARB).

## 10. Stability and Reactivity

**Stability:** Unstable [ ] Stable [ X ]

### Conditions To Avoid - Instability

No data available.

### Incompatibility - Materials To Avoid

Incompatible with oxidizing agents.

### Hazardous Decomposition Or Byproducts

Thermal decomposition may produce carbon monoxide and carbon dioxide.

**Possibility of Hazardous Reactions:** Will occur [ ] Will not occur [ X ]

**Conditions To Avoid - Hazardous Reactions**

No data available.

## 11. Toxicological Information

**Toxicological Information**

HYDROTREATED LIGHT DISTILLATES:

ACUTE TOXICITY:

LC50 Rat Inhalation >3,000 mg/kg

LD50 Rabbit skin 5.5 mg/l 8 hrs

SKIN CORROSION / IRRITATION: Studies on laboratory animals have shown similar materials to cause skin irritation after repeated or prolonged contact. Repeated direct application to the skin can produce defatting dermatitis and kidney damage in laboratory animals. The significance of these animal study results to human health is unclear.

SERIOUS EYE DAMAGE / IRRITATION: Studies on laboratory animals have associated similar materials with eye and respiratory tract irritation.

RESPIRATORY OR SKIN SENSITIZATION: Skin sensitization was not evident in animal studies.

ASPIRATION HAZARD: This material presents an aspiration hazard.

MUTAGENIC DATA: No data.

IMMUNOTOXICITY: No data.

NEUROTOXICITY: Repeated exposure to elevated concentrations of hydrocarbon solvents can produce a variety of transient CNS effects (e.g., dizziness, headache, narcosis, etc.)

DEVELOPMENTAL/REPRODUCTIVE: No data.

CARCINOGEN STATUS: There is inadequate evidence for the carcinogenicity of petroleum solvents in humans.

CAS# 64742-47-8:

Acute toxicity, LC50, Inhalation, Rat, 1400. ppm.

Result:

Behavioral: Hallucinations, distorted perceptions.

Behavioral: Change in motor activity (specific assay).

Behavioral: Changes in psychophysiological tests.

Standard Draize Test, Eyes, Human, 100.0 ppm, Mild.

Result:

Brain and Coverings: Recordings from specific areas of CNS.

Behavioral: Antipsychotic.

Blood: Changes in bone marrow not included above.

**Chronic Toxicological Effects**

No data available.

**Carcinogenicity/Other Information**

ACGIH A4 - Not Classifiable as a Human Carcinogen.

Hazardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
1. Hydrotreated light distillate (petroleum)	64742-47-8	n.a.	n.a.	A4	n.a.

## 12. Ecological Information

**General Ecological Information**

Hydrotreated Light Distillates:

Toxicity: Not toxic to aquatic organisms up to water solubility. May adsorb to sediments and possibly cause toxic effects to organisms.

# SAFETY DATA SHEET

## Klean Strip Odorless Mineral Spirits

Page: 6  
Printed: 01/09/2014  
Revision: 09/27/2010

Persistence and Degradability: Slightly biodegradable in water-based tests due to low water solubility.

Bioaccumulative Potential: No data.

Mobility in Soil: No data.

### Results of PBT and vPvB assessment

CAS# 64742-47-8:

LC50, Bluegill (*Lepomis macrochirus*), 5900. UG/L, 4 D, Mortality, Water temperature: 18 C C, pH: 7.50.

Result:

Age Effects.

- Report to Nalco Chemical Company: Four-Day Static Fish Toxicity Studies with D-2303 in Rainbow Trout and Bluegills: IBT No. A615, Hamlin, J., 1971

LC50, Rainbow Trout (*Oncorhynchus mykiss*), 3200. UG/L, 24 H, Mortality, Water temperature: 55 C C.

Result:

Abnormal development.

- Nalco D-2303: Toxicity to Rainbow Trout (*Salmo gairdneri*): Test No. 423, McCann, J.A., 1971

## 13. Disposal Considerations

### Waste Disposal Method

Dispose in accordance with applicable local, state, and federal regulations.

## 14. Transport Information

### LAND TRANSPORT (US DOT)

**DOT Proper Shipping Name** Paint Related Material, Not Regulated

### Additional Transport Information

For D.O.T. information, contact W.M. Barr Technical Services at 1-800-398-3892.

The shipper / supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

## 15. Regulatory Information

### US EPA SARA Title III

Hazardous Components (Chemical Name)	CAS #	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
1. Hydrotreated light distillate (petroleum)	64742-47-8	No	No	No	No

### Other US EPA or State Lists

Hazardous Components (Chemical Name)	CAS #	CAA HAP,ODC	CWA NPDES	TSCA	CA PROP.65
1. Hydrotreated light distillate (petroleum)	64742-47-8	No	No	Inventory	No

### EPA Hazard Categories:

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

Yes  No Acute (immediate) Health Hazard  
 Yes  No Chronic (delayed) Health Hazard  
 Yes  No Fire Hazard

**SAFETY DATA SHEET**  
**Klean Strip Odorless Mineral Spirits**

Page: 7  
Printed: 01/09/2014  
Revision: 09/27/2010

Yes  No Sudden Release of Pressure Hazard

Yes  No Reactive Hazard

**Regulatory Information Statement**

All components of this material are listed on the TSCA Inventory or are exempt.

**16. Other Information**

**Company Policy or Disclaimer**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

**Revision Date:** 09/27/2010