# SAFETY DATA SHEET

**E**xonMobil

**MOBIL 15W-30** 

### Section 1. Identification

Product name : MOBIL 1 5W-30

Product description : synthetic base stocks and additives

Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** 

: Engine oil

**Uses advised against** 

: This product is not recommended for any industrial, professional or consumer use other

than the identified uses above.

Supplier : EXXON MOBIL CORPORATION

22777 Springwoods Village Parkway

Spring, TX 77389 USA

24-Hour emergency telephone number

: 1-800-424-9300 / +1 703-741-5970 / +1-703-527-3887 (CHEMTREC)

**Product Technical** 

Information

: 800-662-4525

SDS Internet Address : www.sds.exxonmobil.com

### Section 2. Hazards identification

**OSHA/HCS** status

: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.

Classification of the substance or mixture

: Not classified.

Hazards not otherwise

classified

: None known.

Note

: This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

### Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% by weight	CAS number
severely hydrotreated heavy paraffinic distillate	≥50 - ≤75	64742-54-7
severely hydrotreated heavy paraffinic distillate	≥10 - ≤25	64742-54-7
solvent dewaxed heavy paraffinic distillate	≤5	64742-65-0
solvent dewaxed heavy paraffinic distillate	≤3	64742-65-0
benzenamine, n-phenyl-, reaction products with 2,4,4-trimethylpentene	≤3	68411-46-1
organo moly-sulfur complex	≤0.3	1928735-59-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Date of issue/Date of revision : 30 April 2024 Date of previous issue : 17 November 2023 Version : 2.01 1/11

## Section 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

### **Description of necessary first aid measures**

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower **Eye contact** 

eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get

medical attention if symptoms occur.

**Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and

> shoes. Get medical attention if symptoms occur. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate

extent of injury.

Ingestion : Wash out mouth with water. If material has been swallowed and the exposed person is

conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

### Most important symptoms/effects, acute and delayed

### Potential acute health effects

**Eye contact**  No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards.

### Over-exposure signs/symptoms

**Eye contact** : No specific data. Inhalation : No specific data.

Skin contact : Local necrosis as evidenced by delayed onset of pain and tissue damage a few hours

after injection.

: No specific data. Ingestion

### Indication of immediate medical attention and special treatment needed, if necessary

: Treat symptomatically. Contact poison treatment specialist immediately if large Notes to physician

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

### See toxicological information (Section 11)

### Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing

media

: Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing** 

media

: Do not use water jet.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Date of issue/Date of revision : 30 April 2024 Version: 2.01 2/11 Date of previous issue : 17 November 2023

## Section 5. Fire-fighting measures

# Hazardous combustion products

Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume, sulfur oxides

# Special protective actions for fire-fighters

: Use standard firefighting procedures and consider the hazards of other involved materials. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Assure an extended cooling down period to prevent re-ignition. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. No action shall be taken involving any personal risk or without suitable training.

# Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

### **NOTIFICATION PROCEDURES**

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting releases of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800)424-8802.

#### Personal precautions, protective equipment and emergency procedures

# For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

#### For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

### **Small spill**

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Confine the spill immediately with booms. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants. Warn other shipping. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

Date of issue/Date of revision : 30 April 2024 Date of previous issue : 17 November 2023 Version : 2.01 3/11

### Section 7. Handling and storage

### Precautions for safe handling

#### **Protective measures**

Put on appropriate personal protective equipment (see Section 8). Avoid contact with used product.

### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### **Static Accumulator**

This material is a static accumulator. A liquid is typically considered a nonconductive, static accumulator if its conductivity is below 100 pS/m (100x10E-12 Siemens per meter) and is considered a semiconductive, static accumulator if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semiconductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, anti-static additives and filtration can greatly influence the conductivity of a liquid.

### including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

### **Control parameters**

**Occupational exposure limits** 

Ingredient name	Exposure limits
severely hydrotreated heavy paraffinic distillate	ACGIH TLV (United States, 1/2022). [Mineral Oil, pure, highly and severely refined]  TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction  ACGIH TLV (United States, 1/2023). [Mineral Oil, pure, highly and severely refined]  TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction  NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]  TWA: 5 mg/m³ 10 hours. Form: Mist  STEL: 10 mg/m³ 15 minutes. Form: Mist  OSHA PEL (United States, 5/2018). [Oil mist, mineral]  TWA: 5 mg/m³ 8 hours.
severely hydrotreated heavy paraffinic distillate	ACGIH TLV (United States, 1/2023). [Mineral Oil, pure, highly and severely refined]  TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction  NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]  TWA: 5 mg/m³ 10 hours. Form: Mist  STEL: 10 mg/m³ 15 minutes. Form: Mist  OSHA PEL (United States, 5/2018). [Oil mist, mineral]  TWA: 5 mg/m³ 8 hours.
solvent dewaxed heavy paraffinic distillate	ACGIH TLV (United States, 1/2022). [Mineral Oil, pure, highly and severely refined]  TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction  ACGIH TLV (United States, 1/2023). [Mineral Oil, pure, highly and severely refined]  TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction  NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]  TWA: 5 mg/m³ 10 hours. Form: Mist  STEL: 10 mg/m³ 15 minutes. Form: Mist  OSHA PEL (United States, 5/2018). [Oil mist, mineral]

Date of issue/Date of revision 4/11 : 30 April 2024 Date of previous issue : 17 November 2023 Version: 2.01

### Section 8. Exposure controls/personal protection

solvent dewaxed heavy paraffinic distillate

TWA: 5 mg/m<sup>3</sup> 8 hours.

ACGIH TLV (United States, 1/2023). [Mineral Oil, pure, highly and

severely refined]

TWA: 5 mg/m<sup>3</sup> 8 hours. Form: Inhalable fraction

NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]

TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist

OSHA PEL (United States, 5/2018). [Oil mist, mineral]

TWA: 5 mg/m<sup>3</sup> 8 hours.

benzenamine, n-phenyl-, reaction products with

2,4,4-trimethylpentene organo moly-sulfur complex

None.

ACGIH TLV (United States).

TWA: 10 mg/m³ 8 hours. Form: Inhalable fraction TWA: 3 mg/m³ 8 hours. Form: Respirable fraction

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

# Appropriate engineering controls

**Environmental exposure** controls

- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

#### **Skin protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

### Section 9. Physical and chemical properties and safety characteristics

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

Physical state : Liquid.
Color : Amber

Date of issue/Date of revision : 30 April 2024 Date of previous issue : 17 November 2023 Version : 2.01 5/11

## Section 9. Physical and chemical properties and safety characteristics

Odor : Characteristic
Odor threshold : Not available.

pH : Not applicable.

Melting point/freezing point : Not available.

Boiling point, initial boiling

point, and boiling range

: >315.56°C (>600°F)

Flash point : Open cup: >235°C (>455°F) [ASTM D-92]

Evaporation rate : Not available.
Flammability : Ignitable
Lower and upper explosion
limit/flammability limit : Lower: 0.9%
Upper: 7%

Vapor pressure : <0.1 mm Hg [20 °C]

**Relative vapor density** : >2 [Air = 1]

Relative density : 0.855 [ASTM D4052]

Solubility in water : Negligible Partition coefficient: n- : >3.5

octanol/water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : 10.2 cSt [100 °C] [ASTM D 445] 57 cSt [40 °C] [ASTM D 445]

**Particle characteristics** 

Median particle size : Not applicable.

Pour point : -36°C [ASTM D97]

### Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : High energy sources of ignition. Excessive heat.

Incompatible materials : Strong oxidizers

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### Section 11. Toxicological information

### Information on toxicological effects

**Acute toxicity** 

**Conclusion/Summary** 

Inhalation : Minimally Toxic. No end point data for material. Based on assessment of the

components.

**Dermal** : Minimally Toxic. No end point data for material. Based on assessment of the

components.

Oral : Minimally Toxic. No end point data for material. Based on assessment of the

components.

### **Irritation/Corrosion**

Date of issue/Date of revision : 30 April 2024 Date of previous issue : 17 November 2023 Version : 2.01 6/11

### **Section 11. Toxicological information**

### Conclusion/Summary

Skin

: Negligible irritation to skin at ambient temperatures. No end point data for material. Based on assessment of the components.

**Eyes** 

: May cause mild, short-lasting discomfort to eyes. No end point data for material. Based on assessment of the components.

Respiratory

: Negligible hazard at ambient/normal handling temperatures. No end point data for material.

### **Sensitization**

#### Conclusion/Summary

Skin

: Not expected to be a skin sensitizer. No end point data for material. Based on assessment of the components.

Respiratory

: Not expected to be a respiratory sensitizer. No end point data for material.

**Mutagenicity** 

**Conclusion/Summary** 

: Not expected to be a germ cell mutagen. No end point data for material. Based on assessment of the components.

**Carcinogenicity** 

**Conclusion/Summary** 

: Not expected to cause cancer. No end point data for material. Based on assessment of the components.

Reproductive toxicity

**Conclusion/Summary** 

: Not expected to be a reproductive toxicant. No end point data for material. Based on assessment of the components.

### Specific target organ toxicity (single exposure)

**Conclusion/Summary** 

: Not expected to cause organ damage from a single exposure. No end point data for material.

### Specific target organ toxicity (repeated exposure)

**Conclusion/Summary** 

: Not expected to cause organ damage from prolonged or repeated exposure. No end point data for material. Based on assessment of the components.

### **Aspiration hazard**

**Conclusion/Summary** 

: Not expected to be an aspiration hazard. Based on physico-chemical properties of the material. Data available.

### **Other information**

**Contains** 

: Synthetic base oils: Not expected to cause significant health effects under conditions of normal use, based on laboratory studies with the same or similar materials. Not mutagenic or genotoxic. Not sensitizing in test animals and humans. Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (substituted DPA): Results from a supplier's extended one-generation dietary study with 10-week pre-mating administration of substituted DPA included decreased body weight and body weight gains in parental females during gestation and lactation, decreased number of implantation sites and decreased mean litter size. A representative formulation containing substituted DPA was tested in a rat oral gavage reproductive/developmental toxicity screening study (OECD TG 421) with a 10-week pre-mating administration period. Study results included decreased body weight and body weight gain starting in pre-mating and continuing through gestation and lactation in parental females, decreased number of implantation sites and decreasing trend in litter size. A 5 wt% classification threshold for the reproductive effects of substituted DPA was derived based on the NOAEL (50 mg/kg/day) and is consistent with the NOAEL in the supplier's study.

**Product** 

: Component concentrations in this formulation would not be expected to cause skin sensitization, based on tests of the components, this formulation, or similar formulations. Diesel engine oils: Not carcinogenic in animals tests. Used and unused diesel engine oils did not produce any carcinogenic effects in chronic mouse skin painting studies. Oils that are used in gasoline engines may become hazardous and display the following properties: Carcinogenic in animal tests. Caused mutations in vitro. Possible allergen and photoallergen. Contains polycyclic aromatic compounds (PAC) from combustion products of gasoline and/or thermal degradation products.

Date of issue/Date of revision : 30 April 2024 Date of previous issue : 17 November 2023 Version : 2.01 7/11

### **Section 12. Ecological information**

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

#### **Toxicity**

### **Conclusion/Summary**

**Acute toxicity** : Not expected to be harmful to aquatic organisms.

**Chronic toxicity**: Not expected to demonstrate chronic toxicity to aquatic organisms.

#### Persistence and degradability

Not determined.

#### **Bioaccumulative potential**

Not determined.

### **Mobility in soil**

Mobility

: Base oil component -- Expected to partition to sediment and wastewater solids. Low solubility and floats and is expected to migrate from water to the land.

### **Other ecological information**

Other adverse effects

: No known significant effects or critical hazards.

### Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

## **Section 14. Transport information**

<del>-</del>					
	DOT Classification	TDG Classification	IMDG	IATA	
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	
UN proper shipping name	-	-	-	-	
Transport hazard class(es)	-	-	-	-	
Label(s) / Marks					
Packing group	-	-	-	-	
Environmental hazards	No.	No.	No.	No.	

Date of issue/Date of revision : 30 April 2024 Date of previous issue : 17 November 2023 Version : 2.01 8/11

### Section 14. Transport information

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable.

### to IMO instruments

### Section 15. Regulatory information

U.S. Federal regulations

: TSCA 8(a) PAIR: siloxanes and silicones, di-me; naphthalene; diphenylamine

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

Clean Water Act (CWA) 307: 2-pentanol, 4-methyl-, hydrogen phosphorodithioate, zinc salt; phosphorodithioic acid, mixed 0,0 bis (1,3-dimethylbutyl and iso-pr)esters, zinc salts; naphthalene; benzene

Clean Water Act (CWA) 311: fumaric acid; ethylenediamine; naphthalene; vinyl acetate;

benzene

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)**  : Listed

**Clean Air Act Section 602** 

Class I Substances

: Not listed

Clean Air Act Section 602

**Class II Substances** 

: Not listed

**DEA List I Chemicals** 

(Precursor Chemicals)

: Not listed

**DEA List II Chemicals** 

: Not listed

(Essential Chemicals)

### **SARA 302/304**

#### **Composition/information on ingredients**

			SARA 302 TPQ		SARA 304 RQ	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
ethylenediamine vinyl acetate	<0.1 <0.1	Yes. Yes.	10000 1000	1337.1 129	5000 5000	668.5 644.8

**SARA 304 RQ** : 89274873.8 lbs / 40530792.7 kg [12522927.1 gal / 47404435.9 L]

**SARA 311/312** 

Classification : Not applicable.

**SARA 313** 

This material contains no chemicals subject to the supplier notification requirements of the SARA 313 Toxic Release Program.

### State regulations

**Massachusetts** : The following components are listed: OIL MIST, MINERAL; OIL MIST, MINERAL; OIL

MIST, MINERAL; OIL MIST, MINERAL

**New York** : None of the components are listed. **New Jersey** : None of the components are listed. **Pennsylvania** : None of the components are listed. Illinois : None of the components are listed.

### **Inventory list**

Australia inventory (AIIC) : Restrictions Apply

Canada inventory (DSL-NDSL) : All components are listed or exempted.

Date of issue/Date of revision : 30 April 2024 : 17 November 2023 Version: 2.01 9/11 Date of previous issue

## Section 15. Regulatory information

**China inventory (IECSC)** 

Japan inventory (CSCL)

Japan inventory (Industrial Safety and

**Health Act)** 

**New Zealand Inventory of Chemicals** 

(NZIoC)

**Philippines inventory (PICCS)** 

Korea inventory (KECI)

**Taiwan Chemical Substances Inventory** 

(TCSI)

**United States inventory (TSCA 8b)** 

: All components are listed or exempted.

: All components are active or exempted.

### Section 16. Other information

### **Hazardous Material Information System (U.S.A.)**



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

### **National Fire Protection Association (U.S.A.)**



#### Procedure used to derive the classification

Not classified.

### **New Jersey Right to Know Disclosure**

Name	CAS#
Motor Oil	

#### **History**

Date of issue/Date of

revision

: 30 April 2024

Date of previous issue

: 17 November 2023

Version

2.01

Key to abbreviations

: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

Date of issue/Date of revision : 30 April 2024 Date of previous issue : 17 November 2023 Version : 2.01 10/11

### Section 16. Other information

N/A = Not available SGG = Segregation Group UN = United Nations

**References**: Not available.

✓Indicates information that has changed from previously issued version.

Product code : 201510101040\_1276791

**Notice to reader** 

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.